According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 1 of 10

#### **POR-15 SOLVENT**

#### **SECTION 1: Identification**

**Product identifier** 

Product name: POR-15 SOLVENT

**Product code:** POR40401



### Recommended use of the product and restriction on use

Relevant identified uses: Solvent

**Uses advised against:** Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

### Manufacturer or supplier details

Manufacturer: Supplier: United States Australia

P.O.R. Products Sydney Automotive Paints & Equipment Pty Ltd

38 Portman Road A3 / 366 Edgar Street

New Rochelle, NY 10801 Condell Park, NSW 2200 Australia

914-636-0700 +61 2 9772 9000

#### **Emergency telephone number:**

Australia

**Emergency telephone AU Poison Information Centre 13 11 26** 

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST) Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

# SECTION 2: Hazard(s) identification

### **GHS** classification:

Flammable liquids, category 3

Aspiration hazard, category 1

Specific target organ toxicity - single exposure, category 3, respiratory irritation Specific target organ toxicity - single exposure, category 3, central nervous system

Carcinogenicity, category 2

#### **Label elements**

# **Hazard pictograms:**







Signal word: Danger

# **Hazard statements:**

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

# **Precautionary statements:**

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 2 of 10

#### **POR-15 SOLVENT**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/light/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use agents recommended in section 5 for extinction.

P331 Do not induce vomiting.

P301+P310 If swallowed: Immediately call a poison center or doctor/physician.

P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Call a poison center or doctor/physician if you feel unwell.

P308+P313 If exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents and container as instructed in Section 13.

#### Hazards not otherwise classified: None

## **SECTION 3: Composition and information on ingredients**

Identification	Name	Weight Ok
CAS number: 64742-95-6	Solvent naphtha (petroleum), light arom.	100
CAS number: 95-63-6	**1, 2, 4-Trimethylbenzene	<35
CAS number: 1330-20-7	**Xylene	<3
CAS number: 98-82-8	**Cumene	<2

#### **Additional Information:**

\*\* Xylene, Cumene and 1, 2, 4-Trimethylbenzene are components present in the light aromatic naphtha complex, and because they present unique health and environmental hazards, they are listed separately here for clarity.

## **SECTION 4: First aid measures**

# **Description of first aid measures**

## **General notes:**

Get medical attention if you feel unwell

#### After inhalation:

Take precautions to ensure your own safety

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 3 of 10

#### **POR-15 SOLVENT**

Remove source of exposure or move person to fresh air Get medical advice if you feel unwell or concerned

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

# After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes If symptoms develop or persist, seek medical attention

### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

# Most important symptoms and effects, both acute and delayed

### **Acute symptoms and effects:**

Not determined or not applicable.

### **Delayed symptoms and effects:**

Not determined or not applicable.

### Immediate medical attention and special treatment

### **Specific treatment:**

Not determined or not applicable.

#### Notes for the doctor:

If ingested, may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately

# **SECTION 5: Fire fighting measures**

#### **Extinguishing media**

### Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

#### **Unsuitable extinguishing media:**

Do not use a water stream as an extinguisher

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

### **Special protective equipment for firefighters:**

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### **Special precautions:**

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: 3Y

### **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 4 of 10

#### **POR-15 SOLVENT**

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

### **Environmental precautions:**

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and explosion-proof equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

## **Reference to other sections:**

Not determined or not applicable.

# SECTION 7: Handling and storage precautions

### **Precautions for safe handling:**

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

### **Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	**Xylene		TWA: 350 mg/m³ (80 ppm); STEL: 655 mg/m³ (150 ppm)
	**Cumene		TWA: 125 mg/m³ (25 ppm); STEL: 375 mg/m³ (75 ppm)

#### **Biological limit values:**

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

# **Appropriate engineering controls:**

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or

According to the Australian Work Health and Safety Regulations

Date of compilation: 19.06.2023 V2\_AUS Page 5 of 10

#### **POR-15 SOLVENT**

#### handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

#### **Personal protection equipment**

## Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

### **Respiratory protection:**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

#### **SECTION 9: Physical and chemical properties**

## Information on basic physical and chemical properties

Appearance	Clear colorless liquid
Odor	Aromatic
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	-14°C (7°F)
Initial boiling point/range	161°C (322°F) - 171°C (340°F)
Flash point (closed cup)	46°C (115°F) [ASTM D-56]
Evaporation rate	0.27 (n-butyl acetate=1)
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	6.2
Lower flammability/explosive limit	0.9
Vapor pressure	0.269 kPa (2.02 mmHg) at 20°C I 0.815 kPa (6.13 mmHg) at 38°C
Vapor density	4.2 at 101 kPa (Air=1)
Density	873 kg/m³ (7.29 lb/gal, 0.87 kg/dm³) at 15°C
Relative density	0.874 at 15.6°C
Solubilities	Negligible solubility in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	485°C (905°F)
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	0.75 cSt (0.75 mm²/s) at 40°C I 0.9 cSt (0.9 mm²/s) at 25°C
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 6 of 10

#### **POR-15 SOLVENT**

#### Other information

## **SECTION 10: Stability and reactivity**

#### Reactivity:

Does not react under normal conditions of use and storage.

#### **Chemical stability:**

Stable under normal conditions of use and storage.

# Possibility of hazardous reactions:

None under normal conditions of use and storage.

#### **Conditions to avoid:**

Avoid heat, sparks, open flames and other sources of ignition.

## **Incompatible materials:**

Strong oxidizing agents.

Nitric acid.

Sulfuric acid.

## **Hazardous decomposition products:**

None known.

## **SECTION 11: Hazard information**

#### **Acute toxicity**

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

#### Substance data:

Name	Route	Result
**Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
**1, 2, 4-Trimethylbenzene	inhalation	LC50 - Rat - 18,000 mg/m <sup>3</sup>

#### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** 

No data available.

#### Substance data:

Name	Result
**Xylene	Irritating to the skin.
**1, 2, 4-Trimethylbenzene	Irritating to the skin.

## Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

Product data:

No data available.

#### Substance data:

Name	Result
**1, 2, 4-Trimethylbenzene	Irritating effect on the eyes.

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 7 of 10

## **POR-15 SOLVENT**

## Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

Product data:
No data available.
Substance data:

Name	Result
**Cumene	No skin irritation
	No eye irritation

## Carcinogenicity

**Assessment:** Suspected of causing cancer

Product data: No data available.

Substance data:

Name	Species	Result
Solvent naphtha (petroleum), light arom.	Solvent naphtha (petroleum), light arom.	Component may cause cancer.

#### **International Agency for Research on Cancer (IARC):**

Name	Classification
**Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
**Cumene	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP): None of the ingredients are listed.

#### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Solvent naphtha (petroleum),	May cause genetic defects.
light arom.	

#### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

#### Specific target organ toxicity (single exposure)

Assessment: May cause respiratory irritation May cause drowsiness or dizziness

Product data: No data available. Substance data:

Name	Result
**Cumene	Component affects the respiratory system.
**1, 2, 4-Trimethylbenzene	Component affects the respiratory system.

# Specific target organ toxicity (repeated exposure)

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 8 of 10

#### **POR-15 SOLVENT**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**No data available.

Substance data: No data available.

**Aspiration toxicity** 

**Assessment:** May be fatal if swallowed and enters airways

**Product data:**No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics: No

data available.

Other information:

No data available.

# **SECTION 12: Ecological information**

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
**Cumene	EC50 - Daphnia magna - 1.4 mg/L - 24 h
	LC50 - Pimephales promelas - 6.32 mg/L - 96 h
**1, 2, 4-Trimethylbenzene	LC50 - Pimephales promelas - 7.72 mg/L - 96 h

#### Chronic (long-term) toxicity

**Product data:** No data available. **Substance data:** No data available.

# Persistence and degradability

**Product data:** No data available. **Substance data:** No data available.

### **Bioaccumulative potential**

**Product data:** No data available. **Substance data:** No data available.

### Mobility in soil

**Product data:** No data available. **Substance data:** No data available.

Other adverse effects: No data available.

# **SECTION 13: Disposal considerations**

# **Disposal methods:**

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

According to the Australian Work Health and Safety Regulations Date of compilation: 19.06.2023 V2\_AUS Page 9 of 10

# **POR-15 SOLVENT**

# **SECTION 14: Transport information**

## Australian Dangerous Goods (ADG)

UN number	1268
UN proper shipping name	Petroleum Distillates, N.O.S. (Solvent naphtha (petroleum), light aromatic)
UN transport hazard class(es)	3
Packing group	III
Environmental hazards	None
Special precautions for user	None
Hazchem/Emergency Action Code	3Y

# **International Maritime Dangerous Goods (IMDG)**

UN number	1268		
UN proper shipping name	Petroleum Distillates, N.O.S. (Solvent naphtha (petroleum), light aromatic)		
UN transport hazard class(es)	3		
Packing group	III		
Environmental hazards			
Special precautions for user	None		
EmS number	F-E, S-E		
Excepted quantities	El		
Limited quantity	5L		

# International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1268		
UN proper shipping name	Petroleum Distillates, N.O.S. (Solvent naphtha (petroleum), light aromatic)		
UN transport hazard class(es)	3		
Packing group	III		
Environmental hazards			
Special precautions for user	None		
Excepted quantities	El		
imited quantity 10L			

# **SECTION 15: Regulatory information**

According to the Australian Work Health and Safety Regulations

**Date of compilation:** 19.06.2023 V2\_AUS Page 10 of 10

#### **POR-15 SOLVENT**

#### **Australia regulations**

# **Australian Inventory of Industrial Chemicals (AIIC):**

1330-20-7	**Xylene	Listed
64742-95-6	Solvent naphtha (petroleum), light arom.	Listed
98-82-8	**Cumene	Listed
95-63-6	**1, 2, 4-Trimethylbenzene	Listed

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

г			
	1330-20-7	**Xylene	Listed

#### **SECTION 16: Other information**

#### **Abbreviations and Acronyms: None**

#### **Disclaimer:**

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-2-0 **HMIS:** 2-2-0

**Initial preparation date: 22.12.2016** 

**Additional information:** 

Version: 1.0

**End of Safety Data Sheet**