According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

SECTION 1: Identification

Product identifier Product name: Engine Enamel FORD CLASSIC RED Product code: 42098



Recommended use of the product and restriction on use Relevant identified uses: Coating compound/ Surface coating/ paint Uses advised against: Not determined or not applicable. Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer: United States P.O.R. Products 38 Portman Road 914-636-0700 www.PORproducts.com

Supplier: Australia Sydney Automotive Paints & Equipment Pty Ltd A3 / 366 Edgar Street New Rochelle, NY 10801 Condell Park, NSW 2200 Australia +61 2 9772 9000

Emergency telephone number:

Australia

AU Poison Information Centre 13 11 26 General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST) Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3 Skin sensitization, category 1 Specific target organ toxicity - repeated exposure, category 1 Carcinogenicity, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

H351 Suspected of causing cancer.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves/protective clothing/eye protection/face protection. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P281 Use personal protective equipment as required. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P370+P378 In case of fire: Use appropriate fire extinguishing methods for extinction. P321 Specific treatment (see first aid instructions on this label). P363 Wash contaminated clothing before reuse P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or a rash occurs: Get medical advice/attention P362+P364 Take off contaminated clothing and wash it before reuse. P314 Get medical advice/attention if you feel unwell P308+P313 If exposed or concerned: Get medical advice/attention P403+P235 Store in a well ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container according to local regulations. Hazards not otherwise classified: None

SECTION 3: Composition and information on ingredients

Identification	Name	Weight %
CAS number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	<3
CAS number: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<0.1
CAS number: 108-65-6	1-Methoxy-2-propanol acetate	<3
CAS number: 1309-37-1	Diiron trioxide	<2
CAS number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<0.3
CAS number: 96-29-7	Methyl ethyl ketoxime	<0.1
CAS number: 8052-41-3	Stoddard Solvent	33-36

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position Maintain an unobstructed airway Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water If symptoms develop or persist, seek medical attention

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes If symptoms develop or persist, seek medical attention

After swallowing:

Rinse mouth thoroughly Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors Vapors can flow to distant ignition sources and flashback Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Shut off sources of ignition Carbon monoxide and carbon dioxide may form upon combustion Heating causes a rise in pressure, risk of bursting and combustion Hazchem: •3Y

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation Ensure air handling systems are operational Wear protective eye wear, gloves and clothing Beware of vapors accumulating to form explosive concentrations Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing Use spark-proof tools and explosion-proof equipment Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders) Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation. Avoid breathing mist or vapor. Do not eat, drink, smoke or use personal products when handling chemical substances. Take precautionary measures against electrostatic discharges. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Protect from freezing and physical damage.
- Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Australia	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	TWA: 790 mg/m³
	1-Methoxy-2-propanol acetate	108-65-6	TWA: 274 mg/m³ (50 ppm)
	1-Methoxy-2-propanol acetate	108-65-6	STEL: 548 mg/m ³ (100 ppm)

Occupational Exposure limit values:

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Stoddard Solvent	8052-41-3	Time weighted average: 790 mg/m ³
	Diiron trioxide	1309-37-1	TWA: 5 mg/m ³
	1-Methoxy-2-propanol acetate	108-65-6	TWA: 274 mg/m ³ (50 ppm); STEL: 548 mg/m ³ (100 ppm)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Red Colored Liquid
Odor	Solvent-like
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>284°F (>140°C)
Flash point (closed cup)	>105°F (>41°C)
Evaporation rate	Not determined or not available.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	0.848-0.945 g/cm³
Relative density	Not determined or not available.
Solubilities	Not miscible.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Product is not self-igniting
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Oxidizing properties	Not determined or not available.

Other information

60-68%	(Max - < 430 g/L)
--------	-------------------

SECTION 10: Stability and reactivity

Reactivity:

VOC Content

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

Develops readily flammable gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Can react violently with oxygen rich (oxidizing) materials.

Toxic fumes may be released if heated above the decomposition point.

Used empty containers may contain product gases which form explosive mixtures with air.

Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition. Store away from oxidizing agents.

Incompatible materials:

None known.

Hazardous decomposition products:

CO, CO₂. Hydrocarbons.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Irritating to the skin.
Cobalt bis(2-ethylhexanoate)	Irritating to the skin.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Methyl ethyl ketoxime	Risk of serious damage to the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Methyl ethyl ketoxime	May cause sensitization by skin contact
Cobalt bis(2-ethylhexanoate)	May cause sensitization by skin contact.

Carcinogenicity

Assessment: Suspected of causing cancer

Product data: No data available.

Substance data:

Name	Species	Result
Stoddard Solvent	Stoddard Solvent	Component may cause cancer.
Naphtha (petroleum), hydrotreated heavy		May cause cancer.
Methyl ethyl ketoxime		May cause cancer.
Naphtha (petroleum), hydrodesulfurized heavy	Naphtha (petroleum), hydrodesulfurized heavy	Component may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Stoddard Solvent	Group 3
Diiron trioxide	Group 3 - Not classifiable as to its carcinogenicity to humans
Cobalt bis(2-ethylhexanoate)	Group 2B

National Toxicology Program (NTP):

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 8 of 11

Engine Enamel FORD CLASSIC RED

Name	Classification
Cobalt bis(2-ethylhexanoate)	Reasonably anticipated to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent	May cause genetic defects.
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Naphtha (petroleum), hydrodesulfurized heavy	May cause genetic defects.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	Component affects the central nervous system.
Naphtha (petroleum), hydrodesulfurized heavy	Component affects the central nervous system.

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent	Causes damage to organs through prolonged or repeated exposure.
	Causes damage to organs in central nervous system (CNS) through prolonged or repeated exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

Name	Result
Stoddard Solvent	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airway.
Naphtha (petroleum), hydrodesulfurized heavy	May be fatal if swallowed and enters airways.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics: No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent	NOEC Fish: 0.14 mg/L (96 Hr)
Cobalt bis(2-ethylhexanoate)	NOEC - Pimephales promelas - 0.21 mg/L - 34 d

Persistence and degradability

Product data: No data available. Substance data: No data available.

Bioaccumulative potential

Product data: No data available. **Substance data:** No data available.

Mobility in soil

Product data: No data available. **Substance data:** No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Engine Enamel FORD CLASSIC RED

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3
Packing group	
Environmental hazards	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
Special precautions for user	None
Hazchem/Emergency Action Code	•3Y

International Maritime Dangerous Goods (IMDG)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3
Packing group	III
Environmental hazards	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
Special precautions for user	None
EmS number	F-E, S-E
Stowage category	A
Excepted quantities	E1
Limited quantity	5L

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	1263
UN proper shipping name	Paint
UN transport hazard class(es)	3
Packing group	III
Environmental hazards	Marine Pollutant (Stoddard Solvent, Naphtha (petroleum), hydrotreated heavy)
Special precautions for user	None
ERG code	3L
Excepted quantities	E1
Passenger and cargo	60L
Cargo aircraft only	220L
Limited quantity	10L

SECTION 15: Regulatory information

According to the Australian Work Health and Safety Regulations

Initial preparation date: 04.24.2018

Page 11 of 11

Engine Enamel FORD CLASSIC RED

Australia regulations

8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
96-29-7	Methyl ethyl ketoxime	Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
ndard for the l	Iniform Scheduling of Medicines and Poisons (SUSMP):	
8052-41-3	Stoddard Solvent	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
96-29-7	Methyl ethyl ketoxime	Listed
1309-37-1	Diiron trioxide	Listed
108-65-6	1-Methoxy-2-propanol acetate	Not Listed
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Not Listed
136-52-7	Cobalt bis(2-ethylhexanoate)	Not Listed

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-2-0

HMIS: 2-2-0

Initial preparation date: 04.24.2018

Additional information:

Version 1.1

End of Safety Data Sheet