



Safety Data Sheet

acc. to Safe Work Australia - Code of Practice

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **POR-15 RUBBERIZED UNDERCOATING AEROSOL**
Product code(s) **POR49308**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses **General use**

1.3 Details of the supplier of the safety data sheet

Manufacturer:
P.O.R. Products:
38 Portman Road:
New Rochelle:
NY 10801:
United States:
support@porproducts.com:
www.porproducts.com:

Supplier of Product: Sydney Automotive Paints & Equipment Pty Ltd
A3/ 366 Edgar Street
Condell Park, NSW 2200 Australia
+61 2 9772 9000:

1.4 Emergency telephone number

Australia (Mon - Fri, 08:00-16:00 AEST) **General Medical Information: +61 2 9772 9000**
Transport Information: +61 2 9772 9000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|---|----------|---------------------------|------------------|
| 2.3 | aerosols | 1 | Aerosol 1 | H222,H229 |
| 3.2 | skin corrosion/irritation | 2 | Skin Irrit. 2 | H315 |
| 3.5 | germ cell mutagenicity | 1B | Muta. 1B | H340 |
| 3.6 | carcinogenicity | 1A | Carc. 1A | H350 |
| 3.7 | reproductive toxicity | 2 | Repr. 2 | H361d |
| 3.8D | specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |
| 3.9 | specific target organ toxicity - repeated exposure | 2 | STOT RE 2 | H373 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling

- Signal word **danger**

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

| | |
|-------|--|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurized container: may burst if heated. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

- Precautionary statements

| | |
|-----------|--|
| P201 | Obtain special instructions before use. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Pressurized container: Do not pierce or burn, even after use. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

- Hazardous ingredients for labelling VM&P Naptha, toluene, n-butane, propane

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|-------------------|----------------------|-----------|--|
| calcium carbonate | CAS No 471-34-1 | 25 – < 50 | Acute Tox. 4 / H332 |
| toluene | CAS No 108-88-3 | 10 – < 25 | Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 |
| VM&P Naptha | CAS No 64742-89-8 | 10 – < 25 | Flam. Liq. 1 / H224 Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 |
| talc | CAS No 14807-96-6 | 5 – < 10 | Acute Tox. 4 / H332 |

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|-------------------|--------------------|----------|--|
| propane | CAS No 78-93-3 | 5 – < 10 | Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336 |
| n-butane | CAS No 106-97-8 | 1 – < 5 | Flam. Gas 1A / H220 Press. Gas C / H280 Muta. 1B / H340 Carc. 1A / H350 |

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|---|------------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|-------------------|--------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| AU | butane | 106-97-8 | WES | 800 | 1,900 | | | | | | WES |
| AU | toluene | 108-88-3 | WES | 50 | 191 | 150 | 574 | | | | WES |
| AU | talc | 14807-96-6 | WES | | 2.5 | | | | | no_asb | WES |
| AU | Calcium carbonate; Limestone, Marble, Whiting | 471-34-1 | WES | | 10 | | | | | i, noAsb_less1Sil | WES |
| AU | methyl ethyl ketone (MEK) (2-butanone) | 78-93-3 | WES | 150 | 445 | 300 | 890 | | | | WES |
| AU | asphalt (bitumen) | 8052-42-4 | WES | | 5 | | | | | fume | WES |

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

fume as fume

i inhalable fraction

no_asb containing no asbestos fibres

noAsb_less1S contains no asbestos and less than 1% free crystalline silica

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

| Relevant DNELs of components of the mixture | | | | | | |
|---|------------|----------|------------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| calcium carbonate | 471-34-1 | DNEL | 6.36 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| toluene | 108-88-3 | DNEL | 192 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| toluene | 108-88-3 | DNEL | 384 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| toluene | 108-88-3 | DNEL | 192 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| toluene | 108-88-3 | DNEL | 384 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| toluene | 108-88-3 | DNEL | 384 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| talc | 14807-96-6 | DNEL | 2.16 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| talc | 14807-96-6 | DNEL | 2.16 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| talc | 14807-96-6 | DNEL | 3.6 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

| Relevant DNELs of components of the mixture | | | | | | |
|---|------------|----------|-----------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| talc | 14807-96-6 | DNEL | 3.6 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| talc | 14807-96-6 | DNEL | 43.2 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| propane | 78-93-3 | DNEL | 600 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| propane | 78-93-3 | DNEL | 1,161 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components of the mixture | | | | | | |
|---|------------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| toluene | 108-88-3 | PNEC | 0.68 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| toluene | 108-88-3 | PNEC | 0.68 mg/l | aquatic organisms | marine water | short-term (single instance) |
| toluene | 108-88-3 | PNEC | 13.61 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| toluene | 108-88-3 | PNEC | 16.39 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| toluene | 108-88-3 | PNEC | 16.39 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| toluene | 108-88-3 | PNEC | 2.89 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| talc | 14807-96-6 | PNEC | 598 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| talc | 14807-96-6 | PNEC | 141.3 mg/l | aquatic organisms | marine water | short-term (single instance) |
| talc | 14807-96-6 | PNEC | 31.33 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| talc | 14807-96-6 | PNEC | 3.13 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| propane | 78-93-3 | PNEC | 55.8 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| propane | 78-93-3 | PNEC | 55.8 mg/l | aquatic organisms | marine water | short-term (single instance) |
| propane | 78-93-3 | PNEC | 709 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| propane | 78-93-3 | PNEC | 284.7 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

| Relevant PNECs of components of the mixture | | | | | | |
|---|---------|----------|-----------------|-----------------------|---------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| propane | 78-93-3 | PNEC | 284.7 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| propane | 78-93-3 | PNEC | 22.5 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | liquid, solid, gaseous (spray aerosol) |
| Colour | not determined |
| Odour | characteristic |
| Melting point/freezing point | not determined |
| Boiling point or initial boiling point and boiling range | -161.5 °C at 1,013 hPa |
| Flammability | flammable aerosol in accordance with GHS criteria |
| Lower and upper explosion limit | 1.1 vol% - 15 vol% |

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

| | |
|---------------------------|---|
| Flash point | -88.6 °C at 1,013 hPa |
| Auto-ignition temperature | ≥280 °C (auto-ignition temperature (liquids and gases)) |
| Decomposition temperature | not relevant |
| pH (value) | not determined |
| Kinematic viscosity | not relevant |
| Solubility(ies) | not determined |

Partition coefficient

| | |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

| | |
|-----------------|---------------------|
| Vapour pressure | ≤240 kPa at 37.8 °C |
|-----------------|---------------------|

Density and/or relative density

| | |
|-------------------------|---|
| Density | not determined |
| Relative vapour density | information on this property is not available |

| | |
|--------------------------|------------------------|
| Particle characteristics | not relevant (aerosol) |
|--------------------------|------------------------|

9.2 Other information

Information with regard to physical hazard classes

Aerosols

| | |
|--------------------------|------|
| - Components (flammable) | 25 % |
|--------------------------|------|

Other safety characteristics

| | |
|--------------------|------|
| Solid content | 69 % |
| Propellant content | 2 % |

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed, in contact with skin or if inhaled.

| Acute toxicity estimate (ATE) of components of the mixture | | | |
|--|------------|-----------------------|--------------|
| Name of substance | CAS No | Exposure route | ATE |
| calcium carbonate | 471-34-1 | inhalation: dust/mist | >3 mg/l/4h |
| talc | 14807-96-6 | inhalation: dust/mist | >2.1 mg/l/4h |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

| | |
|-----------|---------|
| UN RTDG | UN 1950 |
| IMDG-Code | UN 1950 |
| ICAO-TI | UN 1950 |

14.2 UN proper shipping name

| | |
|-----------|---------------------|
| UN RTDG | AEROSOLS |
| IMDG-Code | AEROSOLS |
| ICAO-TI | Aerosols, flammable |

14.3 Transport hazard class(es)

| | |
|-----------|-----|
| UN RTDG | 2.1 |
| IMDG-Code | 2.1 |
| ICAO-TI | 2.1 |

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria

Packing Instruction: P003

UN Number: 1950, AEROSOLS Hazchem Code: 2YE Special Provisions: 63, 190, 277 Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product. Dangerous Goods Class: Class 2.1: Flammable gases. Packing Group: Not set Packing Instruction: P003 Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

Transport information - National regulations - Additional information (UN RTDG)

| | |
|-----------------|------|
| UN number | 1950 |
| Class | 2.1 |
| Danger label(s) | 2.1 |



POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

| | |
|--------------------------|--|
| Special provisions (SP) | 63, 190, 277, 327, 344, 381, 959 (UN RTDG) |
| Excepted quantities (EQ) | E0 (UN RTDG) 1 |
| Limited quantities (LQ) | L (UN RTDG) |

International Maritime Dangerous Goods Code (IMDG) - Additional information

| | |
|------------------|-----|
| Marine pollutant | - |
| Danger label(s) | 2.1 |



| | |
|--------------------------|----------------------------------|
| Special provisions (SP) | 63, 190, 277, 327, 344, 381, 959 |
| Excepted quantities (EQ) | E0 |
| Limited quantities (LQ) | 1 L |
| EmS | F-D, S-U |
| Stowage category | - |

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

| | |
|-----------------|-----|
| Danger label(s) | 2.1 |
|-----------------|-----|



| | |
|--------------------------|------------|
| Special provisions (SP) | A145, A167 |
| Excepted quantities (EQ) | E0 |
| Limited quantities (LQ) | 30 kg |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations (Australia)

Australian Inventory of Industrial Chemicals (AIIC)

| Australian Inventory of Industrial Chemical Substances | |
|---|------------|
| Name acc. to inventory | CAS No |
| 2-butanone | 78-93-3 |
| butane | 106-97-8 |
| Carbonic acid, calcium salt (1:1) | 471-34-1 |
| Talc (Mg ₃ H ₂ (SiO ₃) ₄) | 14807-96-6 |
| Solvent naphtha, petroleum, light aliphatic | 64742-89-8 |

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to Safe Work Australia - Code of Practice

POR-15 RUBBERIZED UNDERCOATING AEROSOL

Version number: GHS 1.0_AUS

Date of compilation: 19-06-2023

SECTION 16: Other information

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.