



Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Date of issue:23/11/2018

Revision date:20/01/24

Version: 2.0

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Name : Roar 610 Extreme Cut

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Polishes and wax blends

1.4. Supplier's details

Sydney Automotive Paint and Equipment Pty Ltd
Unit A3 366 Edgar Street
NSW 2200 Condell Park - Australia
T +61 2 9772 9000
reception@sape.com.au

1.5. Emergency phone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	Australia Poisons Information Centre	Locked Bag 4001 NSW 2145 Westmead	131126 (27/7 in Australia)	

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Not classified

2.2. Label elements

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
ALUMINA ()	1344-28-1	30 - 50	Not classified
Water ()	7732-18-5	10 - 30	Not classified
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] ()	64742-48-9	10 - 30	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
White mineral oil, petroleum ()	8042-47-5	1 - 10	Asp. Tox. 1, H304
GLYCERIN ()	56-81-5	1 - 10	Not classified
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] ()	64742-82-1	1 - 10	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).] ()	64742-94-5	1 - 10	Asp. Tox. 1, H304

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Castor oil ()	8001-79-4	1 - 10	Not classified
Distillates (petroleum), hydrotreated middle; Gasoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] ()	64742-46-7	1 - 10	Carc. 1B, H350
Terpineol ()	8000-47-1	0.1 - 1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
sodium hydroxide; caustic soda ()	1310-73-2	< 0.1	Skin Corr. 1A, H314

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

- Symptoms/effects after inhalation : May cause irritation or asthma-like symptoms.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : May cause eye irritation.
Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable.
Explosion hazard : Product is not explosive.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Aluminium Oxide (1344-28-1)		
Australia	Local name	Aluminium oxide (alpha-Alumina (Al ₂ O ₃))
Australia	TWA (mg/m ³)	10 mg/m ³
Australia	Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

Glycerol (56-81-5)		
Australia	Local name	Glycerin mist
Australia	TWA (mg/m ³)	10 mg/m ³
Australia	Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

sodium hydroxide; caustic soda (1310-73-2)		
Australia	Local name	Sodium hydroxide
Australia	OEL - Ceilings (mg/m ³)	2 mg/m ³

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

- Hand protection : Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves, Disposable gloves	Nitrile rubber (NBR)				

- Eye protection : Safety glasses

- Skin and body protection : Wear suitable protective clothing

- Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

- Physical state : Liquid

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Appearance	:	
Colour	:	white
Odour	:	characteristic
Odour threshold	:	No data available
pH	:	8
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point / Freezing point	:	Melting point : Not applicable
Boiling point	:	No data available
Flash point	:	72 °C
Auto-ignition temperature	:	No data available
Flammability (solid, gas)	:	No data available
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	Relative density : 1.35
Solubility	:	No data available
Log Pow	:	No data available
Explosive properties	:	No data available
Explosive limits	:	No data available
VOC content	:	245 g/l
Fat solubility	:	No data available

SECTION 10: Stability and reactivity

Reactivity	:	The product is non-reactive under normal conditions of use, storage and transport. The product is non-reactive under normal conditions of use, storage and transport
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reactions known under normal conditions of use.
Conditions to avoid	:	None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Aluminium Oxide (1344-28-1)	
LD50 oral	> 10000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 2300 mg/l

Glycerol (56-81-5)	
LD50 oral	25000 mg/kg bodyweight
LD50 dermal	> 18700 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	50100 mg/l

Skin corrosion/irritation	:	Not classified pH: 8
Serious eye damage/irritation	:	Not classified pH: 8
Respiratory or skin sensitisation	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified
STOT-repeated exposure	:	Not classified
Aspiration hazard	:	Not classified

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

Water (7732-18-5)	
Log Pow	-1.38
Glycerol (56-81-5)	
LC50 fish 1	> 5000 mg/l
EC50 other aquatic organisms 1	> 10000 mg/l waterflea
EC50 other aquatic organisms 2	> 10000 mg/l
Log Pow	-1.76

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Water (7732-18-5)	
Log Pow	See section 12.1 on ecotoxicology
Glycerol (56-81-5)	
Log Pow	See section 12.1 on ecotoxicology

12.4. Mobility in soil

Water (7732-18-5)	
Log Pow	See section 12.1 on ecotoxicology
Glycerol (56-81-5)	
Log Pow	See section 12.1 on ecotoxicology

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available

Roar 610 Extreme Cut	
Fluorinated greenhouse gases	False
Aluminium Oxide (1344-28-1)	
Fluorinated greenhouse gases	False
Water (7732-18-5)	
Fluorinated greenhouse gases	False
Glycerol (56-81-5)	
Fluorinated greenhouse gases	False
White mineral oil, petroleum (8042-47-5)	
Fluorinated greenhouse gases	False
Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (64742-48-9)	
Fluorinated greenhouse gases	False
Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; [A complex combination of hydrocarbons obtained from a catalytic hydrodesulfurization process. It consists of hydrocarbons having carbon numbers predominantly in the range of C7 through C12 and boiling in the range of approximately 90°C to 230°C (194°F to 446°F).] (64742-82-1)	
Fluorinated greenhouse gases	False
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).] (64742-94-5)	
Fluorinated greenhouse gases	False

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Distillates (petroleum), hydrotreated middle; Gasoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] (64742-46-7)

Fluorinated greenhouse gases : False

Castor oil (8001-79-4)

Fluorinated greenhouse gases : False

sodium hydroxide; caustic soda (1310-73-2)

Fluorinated greenhouse gases : False

Terpineol (8000-47-1)

Fluorinated greenhouse gases : False

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. Proper Shipping Name - Addition

Not applicable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (ADG) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available

Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are registered in the AIIC (Australian Inventory of Industrial Chemicals).

15.2. International agreements

No additional information available

Roar 610 Extreme Cut

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 16: Any other relevant information

Classification:

Not classified	
----------------	--

Full text of H-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.

SDS Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product