

## Section 1 - Identification of The Material and Supplier

**Manufactured by Transtar Autobody Technologies,**

**USA. Distributed in Australia by:**

Sydney Automotive Paint & Equipment

Unit A3, 366 Edgar Street

Condell Park NSW 2200

Tel: (02) 9772 9000

Email: [reception@sape.com.au](mailto:reception@sape.com.au)

**Chemical nature:** Aerosol spray  
**Trade Name:** **Weld Through Primer Copper**  
**Product Code:** TS4333  
**Product Use:** Weld through primer. For professional and industrial use only  
**Creation Date:** **March, 2020**  
**This version issued:** **June, 2023** and is valid for 5 years from this date.

**Poisons Information Centre: Phone 13 1126 from anywhere in Australia**

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Xi, Irritating. T, Toxic. Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

**SUSMP Classification:** S5

**ADG Classification:** Class 2.1: Flammable gases.

**UN Number:** 1950, AEROSOLS



### GHS Signal word: DANGER

Flammable aerosols Category 1  
 Gases under pressure - Compressed gas or Liquefied gas or Dissolved gas  
 Aspiration Hazard Category 1  
 Skin Corrosion/Irritation Category 2  
 Serious eye damage/eye irritation Category 2/2A  
 Specific Target Organ Toxicity - Single Exposure Category 3  
 Specific Target Organ Toxicity - Single Exposure Category 3  
 Carcinogenicity Category 2  
 Reproductive Toxicity Category 1  
 Specific Target Organ toxicity - repeated exposure Category 2

### HAZARD STATEMENT:

H315: Causes skin irritation.  
 H319: Causes serious eye irritation.  
 H351: Suspected of causing cancer.  
 H360: May damage fertility or the unborn child.  
 H335: May cause respiratory irritation.  
 H336: May cause drowsiness or dizziness.  
 H373: May cause damage to organs (central nervous system, respiratory system, eyes, skin, ears, kidney, blood, bone marrow and liver) through prolonged or repeated exposure.  
 H304: May be fatal if swallowed and enters airways.  
 H222: Extremely flammable aerosol  
 H280: Contains gas under pressure; may explode if heated.

### PREVENTION

P201: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.  
 P280: Wear protective gloves, protective clothing and eye or face protection.  
 P264: Wash face, hands and any exposed skin thoroughly after handling.  
 P260: Do not breathe dust, fume, gas, mist, vapours, spray.  
 P271: Use only outdoors or in a well ventilated area.

## SAFETY DATA SHEET

**Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)**

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

#### RESPONSE

P308+P313: If exposed or concerned: Get medical advice, attention.

P321: Specific treatment (see first aid on this label).

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice.

P362: Take off contaminated clothing and wash before reuse.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTRE or doctor, physician if you feel unwell.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician.

P331: Do NOT induce vomiting.

#### STORAGE

P405: Store locked up.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P410: Protect from sunlight.

P412: Do not expose to temperatures exceeding 50°C.

#### DISPOSAL

P501: Dispose of contents, container to an approved waste disposal plant.

### Emergency Overview

**Physical Description & Colour:** Opaque copper-coloured aerosol spray

**Odour:** Solvent odour.

**Major Health Hazards:** may cause serious damage to eyes, may impair fertility, may cause harm to unborn children, irritating to respiratory system and skin, if aspirated, may cause lung damage, vapours may cause drowsiness and dizziness.

### Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Petroleum gases, liquefied, sweetened	68476-86-8	30-40	not set	not set
Methyl acetate	79-20-9	20-30	606	757
n-Butyl acetate	123-86-4	10-20	713	950
Toluene	108-88-3	10-20	191	574
Acetone	67-64-1	1-10	1185	2375
Zinc	7440-66-6	1-10	not set	not set
Other non-hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equaled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g.

### SAFETY DATA SHEET

watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical or foam. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** -96.4°C

**Upper Flammability Limit:** Not available

**Lower Flammability Limit:** Not available

**Autoignition temperature:** No data.

**Flammability Class:** Flammable Category 2 (GHS); Highly Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include polyvinyl alcohol, Teflon, butyl rubber, PE/EVAL or Responder. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions e.g. use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Methyl acetate	606	757
n-Butyl acetate	713	950
Toluene	191	574
Acetone	1185	2375

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles must be worn when this product is being used. Failure to protect your eyes may lead to severe harm to them or to general health. Emergency eye wash facilities must also be available in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: polyvinyl alcohol, Teflon, butyl rubber, PE/EVAL, Responder.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## Section 9 - Physical and Chemical Properties:

**Physical Description & colour:** Opaque copper-coloured aerosol spray

**Odour:** Solvent odour.

**Boiling Point:** Not available.

**Freezing/Melting Point:** No specific data. Liquid at normal temperatures.

**Volatiles:** 54.54%

**Vapour Pressure:** No data.

**Vapour Density:** No data.

**Specific Gravity:** Approx 0.846

**Water Solubility:** No data.

**pH:** No data.

**Volatility:** No data.

**Odour Threshold:** No data.

**Evaporation Rate:** No data.

**Coeff Oil/water Distribution:** No data

**Autoignition temp:** No data.

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** strong acids, strong bases, strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

**Local Effects:**

**Target Organs:** There is no data to hand indicating any particular target organs.

Petroleum Gases, Liquefied, Sweetened is a SWA Class 2 Mutagen, likely to be mutagenic to humans.

Toluene is a SWA Class 1 Reproductive risk, may impair fertility.

### Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Petroleum Gases, Liquefied, Sweetened <ul style="list-style-type: none"> <li>Gasses under pressure</li> <li>Flammable gas – category 1</li> <li>Carcinogenicity – category 1B</li> <li>Germ cell mutagenicity – category 1B</li> </ul>	Conc>=0.1%: T; R45; R46
Methyl Acetate <ul style="list-style-type: none"> <li>Flammable liquid – category 2</li> <li>Eye irritation – category 2</li> <li>Specific target organ toxicity (single exposure) – category 3</li> </ul>	Conc>=20%: Xi; R36
N-butyl Acetate <ul style="list-style-type: none"> <li>Flammable liquid – category 3</li> <li>Specific target organ toxicity (single exposure) – category 3</li> </ul>	
Toluene <ul style="list-style-type: none"> <li>Flammable liquid – category 2</li> <li>Skin irritation – category 2</li> <li>Specific target organ toxicity (repeated exposure) – category 2</li> <li>Reproductive toxicity – category 1A</li> </ul>	>=10%Conc<20%: T; R60; R61; R48/20
Acetone <ul style="list-style-type: none"> <li>Flammable liquid – category 2</li> <li>Eye irritation – category 2A</li> <li>Specific target organ toxicity (single exposure) – category 3</li> </ul>	No risk phrases at concentrations found in this product
Zinc <ul style="list-style-type: none"> <li>Substance or mixture which in contact with water emits flammable gas – category 1</li> <li>Pyrophoric solid – category 1</li> <li>Hazardous to the aquatic environment (acute) – category 1</li> <li>Hazardous to the aquatic environment (chronic) – category 1</li> </ul>	

### Potential Health Effects

#### Inhalation:

**Short Term Exposure:** This product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased if treatment is prompt. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

#### Skin Contact:

**Short Term Exposure:** Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

#### Eye Contact:

**Short Term Exposure:** If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

#### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product is an oral irritant. Symptoms may include burning

sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** Petroleum Gases, Liquefied, Sweetened is classified by SWA as a Category 1b Carcinogen  
See the SWA website for further details. A web address has not been provided as addresses frequently change.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Toluene is Class 3 - unclassifiable as to carcinogenicity to humans.  
See the IARC website for further details. A web address has not been provided as addresses frequently change.

## Section 12 - Ecological Information

Insufficient data to be sure of status.

## Section 13 - Disposal Considerations

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle product and containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Do not puncture or incinerate aerosol cans, even when empty.

## Section 14 - Transport Information

**Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.**

**UN Number:** 1950, AEROSOLS

**Hazchem Code:** 2YE

**Special Provisions:** 63, 190, 277, 327, 344, 381

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

**Dangerous Goods Class:** Class 2.1: Flammable gases.

**Packing Group:** Not set

**Packing Instruction:** P207, LP200

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

## Section 15 - Regulatory Information

**Australia:** AIIC (Australian Inventory of Industrial Chemicals)

All the ingredients are listed or exempt.

## Section 16 - Other Information

**This SDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AIIC</b>	Australian Inventory of Industrial Chemicals
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)