

Section 1 - Identification of The Material and Supplier

Manufactured by Transtar Autobody Technologies, USA

Distributed in Australia by:

Chemical nature: Blend of ingredients.
Trade Name: **Quick Dry Rubberized Undercoat**
Product Code: 4361-F, 4364-F, 4365-F, 4369-F
Product Use: For Professional and Industrial Use Only
Creation Date: **September, 2016**
This version issued: **November, 2021** and is valid for 5 years from this date.
Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Not classified as hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: Class 3, Flammable Liquids.

UN Number: 1139, COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)



GHS Signal word: DANGER

Flammable liquids Category 2
 Aspiration Hazard Category 1
 Skin Corrosion /Irritation Category 2
 Serious eye damage/eye irritation Category 2/2A
 Germ cell mutagenicity Category 1B
 Carcinogenicity Category 1B
 Reproductive Toxicity Category 1A
 Specific Target Organ toxicity - single exposure Category 1
 Specific Target Organ toxicity - repeated exposure Category 1
 Hazardous to aquatic environment Short term/Acute Category 2

HAZARD STATEMENT:

H225: Highly flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H340: May cause genetic defects.
 H350: May cause cancer.
 H360: May damage fertility or the unborn child.
 H370: Causes damage to organs.
 H372: Causes damage to organs through prolonged or repeated exposure.
 H401: Toxic to aquatic life.

GHS Precautions

P101 If medical advice is needed, have product container or label at hand
 P102 Keep out of reach of children
 P103 Read label before use

SAFETY DATA SHEET

P201 Obtain special instructions before use
 P202 Do not handle until all safety precautions have been read and understood
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking
 P233 Keep container tightly closed
 P240 Ground and bond container and receiving equipment
 P241 Use explosion-proof electrical, ventilating, lighting and motorized equipment
 P242 Use only non-sparking tools
 P243 Take precautionary measures against static discharge
 P260 Do not breathe dust, mist, vapors or spray
 P264 Wash contacted skin thoroughly after handling
 P270 Do not eat, drink or smoke when using this product
 P273 Avoid release to the environment
 P280 Wear protective gloves, protective clothing, eye protection, face protection and respiratory protection.
 P321 Specific treatment (see first aid instructions on SDS)
 P331 Do NOT induce vomiting
 P362 Take off contaminated clothing and wash before reuse
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 P303+P361+P353 IF ON SKIN (or hair): Immediately take off all contaminated clothing. Wash skin with soap and water.
 P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
 P307+P311 IF exposed: Call a POISON CENTER or doctor
 P332+P313 If skin irritation occurs: Get medical advice
 P337+P313 If eye irritation persists: Get medical attention.
 P370+P378 In case of fire: Use dry chemical, CO₂, foam or water fog to extinguish
 P405 Store locked up
 P403+P235 Store in a well ventilated place. Keep cool
 P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

Emergency Overview

Physical Description & Colour: Black liquid

Odour: Organic solvent

Major Health Hazards: Exposure can cause respiratory tract and throat irritation, headaches, shortness of breath and symptoms similar to intoxication. Overexposure can produce severe central nervous system depression, coma and respiratory failure.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	67-64-1	20-30	1185	2375
Hexane	110-54-3	17.4	72	not set
Calcium carbonate	1317-65-3	5-10	10	not set
Alkyd copolymer		5-10	not set	not set
Modified pentaerythritol ester of rosin		1-5	not set	not set
Petroleum spirit	64742-89-8	4.6	not set	not set
Organically modified bentonite clay, non-hazardous		1-5	not set	not set
Toluene	108-88-3	1-5	191	574
Carbon black	1333-86-4	1-5	3	not set
Styrene-butadiene block copolymer, non-hazardous		1-5	not set	not set
Xylene	1330-20-7	1-5	350	655
Heptane, all isomers		1-5	not set	not set
Amorphous silica	7631-86-9	1-5	2	not set
Methanol	67-56-1	1-5	262	328
Ethyl benzene	100-41-4	0.1-1.0	434	543
Other non hazardous ingredients	secret	to 100	not set	not set

SAFETY DATA SHEET

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 10 minutes or until chemical is removed. If irritation persists, repeat flushing and obtain medical advice.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. Avoid the use of coarse water spray.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: -22°C

Upper Flammability Limit: Not available

Lower Flammability Limit: Not available

Autoignition temperature: 225°C

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Nitrile, butyl rubber, Teflon, PE/EVAL, Responder. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. Eye/face protective equipment should comprise as a minimum, protective goggles. Eye/face protective equipment should include a full face shield. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions e.g. use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by

SAFETY DATA SHEET

consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool (below 30 °C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	1185	2375
Hexane	72	not set
Calcium carbonate	10	not set
Toluene	191	574
Carbon black	3	not set
Xylene	350	655
Amorphous silica	2	not set
Methanol	262	328
Ethyl benzene	434	543

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is local exhaust ventilation.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: nitrile, butyl rubber, Teflon, PE/EVAL, Responder.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Black liquid
Odour:	Organic solvent
Boiling Point:	56 °C at 100kPa
Freezing/Melting Point:	No data.
Volatiles:	No data.
Vapour Pressure:	15.3648 kPa
Vapour Density:	2.5
Specific Gravity:	0.921
Water Solubility:	No data.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.

SAFETY DATA SHEET

Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	225°C

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers and surrounding areas well ventilated. Under no circumstances should the container be sealed. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: acids, strong oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Calcium compounds, Formaldehyde. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Toxicity: LD₅₀ Oral, Rat 5800mg/kg

LD₅₀ Oral, Mouse = 3000mg/kg

LD₅₀ Oral, Rabbit = 5340mg/kg

LD₅₀ Dermal, Guinea Pig = >9400mg/kg

In Delayed (Chronic and subchronic) studies, an 8 week inhalation study in rats showed no significant effects at 19,000ppm 5 days/week, and a 90 day oral toxicity in rats showed a no-observed-effects-level of 100mg/kg/day and a low-observed-effects-level of 500mg/kg/day based on increased liver and kidney weights and nephrotoxicity.

Ames Assay (*S. typhimium*): Negative

Chromosome Aberrations and Sister Chromatid Exchange Assays: Negative

Point Mutation in Mouse Lymphoma Cells: Negative

DNA Cell-binding Assay: Negative

This product may attack blood cells, central nervous system, kidneys, liver, lungs, skin.

Hexane is a SWA Class 3 Reproductive risk.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Acetone	Conc>=20%: Xi; R36
<ul style="list-style-type: none"> Flammable liquid - category 2 Eye irritation - category 2A Specific target organ toxicity (single exposure) - category 3 	
Hexane	>=5%Conc<20%: Xn; R62; R48/20
<ul style="list-style-type: none"> Flammable liquid - category 2 Reproductive toxicity - category 2 Aspiration hazard - category 1 Specific target organ toxicity (repeated exposure) - category 2 Skin irritation - category 2 Specific target organ toxicity (single exposure) - category 3 Hazardous to the aquatic environment (chronic) - category 2 	
Petroleum Spirit	
<ul style="list-style-type: none"> Aspiration hazard - category 1 	
Toluene	>=0.5%Conc<10%: T; R60; R61
<ul style="list-style-type: none"> Flammable liquid - category 2 Skin irritation - category 2 Specific target organ toxicity (repeated exposure) - category 2 Reproductive toxicity - category 1A 	
Xylene	
<ul style="list-style-type: none"> Flammable liquid - category 3 Acute toxicity - category 4 Acute toxicity - category 4 Specific target organ toxicity (single exposure) - category 3 Skin irritation - category 2 	
Methanol	

SAFETY DATA SHEET

- Flammable liquid - category 2
- Acute toxicity - category 3
- Acute toxicity - category 3
- Specific target organ toxicity (single exposure) - category 1

Ethyl Benzene

- Flammable liquid - category 2
- Acute toxicity - category 4
- Eye irritation - category 2A
- Skin irritation - category 2

Hexane: LD₅₀ Oral, Rat 3000mg/kgLD₅₀ Dermal, Rabbit = 3000mg/kg**Petroleum Spirit:** LD₅₀ Oral, Rat 64742-89-8mg/kgLD₅₀ Dermal, Rabbit = 3000mg/kg**Toluene:** LD₅₀ Oral, Rat 2600mg/kgLC₅₀ Inhalation, Rat = 13mg/L/4hr**Xylene:** LD₅₀ Oral, Rat 3500mg/kgLD₅₀ Dermal, Rabbit = 4350mg/kgLC₅₀ Inhalation, Rat = 29mg/L/4hr**Amorphous Silica:** LD₅₀ Oral, Rat 2000mg/kgLD₅₀ Dermal, Rabbit = 2mg/kg**Ethyl Benzene:** LD₅₀ Oral, Rat 3500mg/kgLC₅₀ Inhalation, Rat = 17mg/L/4hr

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is believed to be mildly irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: This product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 12 - Ecological Information

This product is toxic to aquatic organisms. This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

BOD: 1.22g O₂/g (5 days)

Fish: LC₅₀ rainbow trout: 5540mg/L

LC₅₀ bluegill sunfish: 8300mg/L

Daphnia: EC₅₀ 10mg/L (24-48 hour)

Bioconcentration factor is 1, suggesting bioconcentration in aquatic organisms is low. This was calculated using an experimental Log Kow value of -0.24

Octanol/water partition coefficient: 0.58

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

SAFETY DATA SHEET

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1139, COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle undercoating, drum or barrel lining)

Hazchem Code: •3YE

Special Provisions: None allocated

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packing Group: II

Packing Instruction: P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

Section 15 - Regulatory Information

AIIC: All of the significant ingredients in this formulation are compliant with AICIS regulations.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICIS/AIIC	Australian Industrial Chemicals Introduction Scheme/Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)