

Section 1 - Identification of the Material and Supplier

Manufactured by Transtar Autobody Technologies, USA

Distributed in Australia by:

Sydney Automotive Paint & Equipment

Unit A3, 366 Edgar Street

Condell Park NSW 2200

Tel: (02) 9772 9000

Email: reception@sape.com.au

Chemical nature: Blend of solvents, resin and pigments presented as an aerosol.

Trade Name: 2 IN 1 PRIMER GRAY

Product Code: TS4603

Product Use: Primer. For professional and industrial use only.

Creation Date: October, 2016

This version issued: June, 2023 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. T, Toxic. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: Class 2.1: Flammable gases.

UN Number: 1950, AEROSOLS



GHS Signal word: DANGER

Flammable aerosols Category 1

Gases under pressure - Compressed gas

Skin Irritation Category 2

Serious eye irritation Category 2A

Carcinogenicity Category 2

Reproductive Toxicity Category 2

Specific Target Organ toxicity - single exposure Category 1

Specific Target Organ toxicity - repeated exposure Category 2

HAZARD STATEMENT:

H222: Extremely flammable aerosol

H280: Contains gas under pressure; may explode if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child.

H370: Causes damage to organs (Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Reproductive System, Skin, Central Vascular System and Gastrointestinal Tract) through prolonged or repeated exposure

H373: May cause damage to organs (Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Reproductive System, Skin and Central Vascular System) through prolonged or repeated exposure.

PREVENTION

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 Specific treatment (see first aid on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse.

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national and international regulations. Dispose of contents/container to an approved waste disposal plant.

Emergency Overview

Physical Description & Colour: Grey opaque paint presented as an aerosol.

Odour: Characteristic odour.

Major Health Hazards: Exposure can cause respiratory tract and throat irritation, headaches, shortness of breath and symptoms similar to intoxication. Overexposure can produce severe central nervous system depression, coma and respiratory failure. For this product: limited evidence of a carcinogenic effect, may impair fertility, may cause harm to unborn children, irritating to eyes and skin.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	67-64-1	30-40	1185	2375
Propane/Isobutane/n-Butane	68476-86-8	20-30	not set	not set
Methyl isobutyl ketone	108-10-1	1-10	205	307
Titanium dioxide	13463-67-7	1-10	10	not set
Talc	14807-96-6	1-10	2.5	not set
1-methoxy-2-acetoxypropane	108-65-6	1-10	274	548
Toluene	108-88-3	1-10	191	574
Methanol	67-56-1	1-10	262	328
Isopropanol	67-63-0	1-10	983	1230
n-Butyl acetate	123-86-4	1-10	713	950
Maleic modified resin	secret	1-10	not set	not set
Carbon black	1333-86-4	<1	3	not set
Ethyl benzene	100-41-4	<1	434	543
Zinc oxide	1314-13-2	<1	10 (dust)	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equaled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Quickly and gently wipe or blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. Avoid the use of water jets.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus. Cool closed, undamaged containers exposed to fire with water spray.

Flash point: -96°C (propellant)

Upper Flammability Limit: Not available

Lower Flammability Limit: Not available

Autoignition temperature: No data.

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

Section 6 - Accidental Release Measures

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	1185	2375
Methyl isobutyl ketone	205	307

SAFETY DATA SHEET

Titanium dioxide	10	not set
Talc	2.5	not set
1-methoxy-2-acetoxyp propane	274	548
Toluene	191	574
Methanol	262	328
Isopropanol	983	1230
n-Butyl acetate	713	950
Carbon black	3	not set
Ethyl benzene	434	543
Zinc oxide	10 (dust)	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: There is no data that enables us to recommend any type except that it should be impermeable.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Grey opaque paint presented as an aerosol.

Odour: Characteristic odour.

Boiling Point: Not available.

Freezing/Melting Point: No specific data. Liquid at normal temperatures.

Volatiles: No data. VOC 50%

Vapour Pressure: No data.

Vapour Density: No data.

Specific Gravity: 0.894

Water Solubility: Practically insoluble.

pH: No data.

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: No data.

Coeff Oil/water Distribution: No data

Autoignition temp: No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: strong acids, strong bases, strong oxidising agents, Chlorinated compounds.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

SAFETY DATA SHEET

Section 11 - Toxicological Information

There is no data to hand indicating any particular target organs.

Toluene is a SWA Class 3 Reproductive risk.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Acetone	Conc \geq 20%: Xi; R36
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Eye irritation - category 2A • Specific target organ toxicity (single exposure) - category 3 	
Propane/isobutane/n-butane	No risk phrases at concentrations found in this product
<ul style="list-style-type: none"> • Gas under pressure • Flammable gas - category 1 	
Methyl Isobutyl Ketone	\geq 1%Conc<20%: Xn; R40
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Acute toxicity - category 4 • Carcinogenicity - category 2 • Eye irritation - category 2A • Specific target organ toxicity (single exposure) - category 3 	
1-methoxy-2-acetoxypropane	
<ul style="list-style-type: none"> • Flammable liquid - category 3 	
Toluene	\geq 0.5%Conc<10%: T; R60; R61
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Skin irritation - category 2 • Specific target organ toxicity (repeated exposure) - category 2 • Reproductive toxicity - category 1A 	
Methanol	\geq 3%Conc<10%: Xn; R20/21/22; R68/20/21/22
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Acute toxicity - category 3 • Acute toxicity - category 3 • Acute toxicity - category 3 • Specific target organ toxicity (single exposure) - category 1 	
Isopropanol	
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Eye irritation - category 2A • Specific target organ toxicity (single exposure) - category 3 	
N-butyl Acetate	
<ul style="list-style-type: none"> • Flammable liquid - category 3 • Specific target organ toxicity (single exposure) - category 3 	
Ethyl Benzene	
<ul style="list-style-type: none"> • Flammable liquid - category 2 • Acute toxicity - category 4 • Eye irritation - category 2A • Skin irritation - category 2 	
Zinc Oxide	
<ul style="list-style-type: none"> • Hazardous to the aquatic environment (acute) - category 1 • Hazardous to the aquatic environment (chronic) – category1 	

Chemical Name	LD ₅₀ Oral	LD ₅₀ Dermal	LC ₅₀ Inhalation
Acetone	= 5800 mg/kg (rat)	- =	50100 mg/m ³ (rat) 8 h
Methyl isobutyl ketone	= 2080 mg/kg (rat)	= 3000 mg/kg (rabbit)	= 8.2 mg/L (rat) 4 h
1-methoxy-2-propanol acetate	= 8532 mg/kg (rat)	> 5 g/kg (rabbit) -	
Nitrocellulose resin	> 5 g/kg (rat)	-	-
Titanium dioxide	>10,000mg/kg (rat)	-	-
Xylene	= 3500 mg/kg (rat)	4350 mg/kg (rabbit)	= 29.08 mg/L (rat) 4 h
Toluene	= 2600 mg/kg (rat)	= 12000 mg/kg (rabbit)	= 12.5 mg/L (rat) 4 h

SAFETY DATA SHEET

Methanol	= 6200 mg/kg (rat)	-	= 22500 ppm (rat) 8 h
Isopropyl alcohol	= 1870 mg/kg (rat)	4059 mg/kg (rabbit)	= 72600 mg/m ³ (rat) 4 h
Butyl acetate	= 10768 mg/kg (rat)	> 17600 mg/kg (rabbit)	= 390 ppm (rat) 4 h
Carbon black	> 15400 mg/kg (rat)	-	-
Ethyl benzene	= 3500 mg/kg (rat)	= 15400 mg/kg (rabbit)	= 17.2 mg/L (rat) 4 h
Zinc oxide	> 5000 mg/kg (rat)	-	-

Potential Health Effects

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: Propane/isobutane/n-butane is classified by SWA as a Class 1 Carcinogen, known to be carcinogenic to humans.

See the SWA website for further details. A web address has not been provided as addresses frequently change.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Methyl Isobutyl Ketone is classed 2b IARC - possibly carcinogenic to humans.

Titanium dioxide is classed 2b IARC - possibly carcinogenic to humans.

Talc is Class 3 - unclassifiable as to carcinogenicity to humans.

Toluene is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Acetone		4.74 - 6.33 mg/L LC ₅₀ Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC ₅₀ Pimephales promelas 96h static 8300 mg/L LC ₅₀ Lepomis macrochirus 96h		10294 - 17704 mg/L EC ₅₀ Daphnia magna 48h Static 12600 - 12700 mg/L EC ₅₀ Daphnia magna 48h
Methyl isobutyl ketone	400 mg/L EC ₅₀ Pseudokirchneriella subcapitata 96h	496 - 514 mg/L LC ₅₀ Pimephales promelas 96h flow-through		170 mg/L EC ₅₀ Daphnia magna 48h
Talc		100 g/L LC ₅₀ Brachydanio rerio 96h semi-static		
1-methoxy-2-propanol acetate		161 mg/L LC ₅₀ Pimephales promelas 96h static		500 mg/L EC ₅₀ Daphnia magna 48h
Xylene		13.4 mg/L LC ₅₀ Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC ₅₀ Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC ₅₀ Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC ₅₀		3.82 mg/L EC ₅₀ water flea 48h 0.6 mg/L LC ₅₀ Gammarus lacustris 48h

SAFETY DATA SHEET

		Lepomis macrochirus 96h flow-through 19 mg/L LC ₅₀ Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC ₅₀ Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC ₅₀ Pimephales promelas 96h static 780 mg/L LC ₅₀ Cyprinus carpio 96h semi-static 780 mg/L LC ₅₀ Cyprinus carpio 96h 30.26 - 40.75 mg/L LC ₅₀ Poecilia reticulata 96h static		
Toluene	433 mg/L EC ₅₀ Pseudokirchneriella subcapitata 96h 12.5 mg/L EC ₅₀ Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC ₅₀ Pimephales promelas 96h flow-through 12.6 mg/L LC ₅₀ Pimephales promelas 96h static 5.89 - 7.81 mg/L LC ₅₀ Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC ₅₀ Oncorhynchus mykiss 96h static 5.8 mg/L LC ₅₀ Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC ₅₀ Lepomis macrochirus 96h static 54 mg/L LC ₅₀ Oryzias latipes 96h static 28.2 mg/L LC ₅₀ Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC ₅₀ Poecilia reticulata 96h static		5.46 - 9.83 mg/L EC ₅₀ Daphnia magna 48h Static 11.5 mg/L EC ₅₀ Daphnia magna 48h
Methanol		28200 mg/L LC ₅₀ Pimephales promelas 96h flow-through 100 mg/L LC ₅₀ Pimephales promelas 96h static 19500 - 20700 mg/L LC ₅₀ Oncorhynchus mykiss 96h flow-through 18 - 20 mL/L LC ₅₀ Oncorhynchus mykiss 96h static 13500 - 17600 mg/L LC ₅₀ Lepomis macrochirus 96h flow-through		
Isopropyl alcohol	1000 mg/L EC ₅₀ Desmodesmus subspicatus 96h 1000 mg/L EC ₅₀ Desmodesmus subspicatus 72h	9640 mg/L LC ₅₀ Pimephales promelas 96h flow-through 11130 mg/L LC ₅₀ Pimephales promelas 96h static 1400000 µg/L LC ₅₀ Lepomis macrochirus 96h		13299 mg/L EC ₅₀ Daphnia magna 48h
Butyl acetate	674.7 mg/L EC ₅₀ Desmodesmus subspicatus 72h	100 mg/L LC ₅₀ Lepomis macrochirus 96h static 17 - 19 mg/L LC ₅₀ Pimephales promelas 96h flow-through		
Ethyl benzene	4.6 mg/L EC ₅₀ Pseudokirchneriella subcapitata 72h 438 mg/L EC ₅₀ Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC ₅₀ Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC ₅₀ Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC ₅₀ Oncorhynchus mykiss 96h static 4.2 mg/L LC ₅₀ Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC ₅₀ Pimephales promelas 96h flow-through 32 mg/L LC ₅₀ Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC ₅₀ Pimephales promelas 96h static 9.6 mg/L LC ₅₀ Poecilia reticulata 96h static		Daphnia magna 48h

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service. Do not puncture or incinerate aerosol cans, even when empty.

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1950, AEROSOLS

Hazchem Code: 2YE

Special Provisions: 63, 190, 277

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packing Group: Not set

Packing Instruction: P003

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

Australia: AIIC (Australian Inventory of Industrial Chemicals)

All the ingredients are listed or exempt.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AIIC	Australian Inventory of Industrial Chemicals
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

SAFETY DATA SHEET