

Section 1 - Identification of the Material and Supplier

Manufactured by Transtar Autobody Technologies, USA

Distributed in Australia by:

Sydney Automotive Paint & Equipment

Unit A3, 366 Edgar Street

Condell Park NSW 2200

Tel: (02) 9772 9000

Email: reception@sape.com.au

Chemical nature: Aerosol containing resins and pigments.
Trade Name: 2-in-1 Primer White
Product Code: TS4633
Product Use: Primer for professional and industrial use.
Creation Date: August, 2016
This version issued: June, 2023 and is valid for 5 years from this date.
Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. T, Toxic. F+, Highly Flammable. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: Class 2.1: Flammable gases.

UN Number: 1950, AEROSOLS



GHS Signal word: DANGER

Flammable aerosols Category 1

Gases under pressure - Compressed gas

Skin Irritation Category 2

Skin Sensitisation Category 1

Serious eye eye irritation Category 2A

Specific Target Organ Toxicity - Single Exposure Category 3. Transient target organ effects- Narcotic effects

Germ cell mutagenicity Category 1B.

Carcinogenicity Category 2

Reproductive Toxicity Category 1

Specific Target Organ toxicity - repeated exposure Category 2

HAZARD STATEMENT:

H222: Extremely flammable aerosol

H280: Contains gas under pressure; may explode if heated.

AUH066: Repeated exposure may cause skin dryness or cracking.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H351: Suspected of causing cancer.

H360: May damage fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

GHS Precautions

P101 If medical advice is needed, have product container or label at hand

P102 Keep out of reach of children

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

P103 Read label before use
 P201 Obtain special instructions before use
 P202 Do not handle until all safety precautions have been read and understood
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking
 P211 Do not spray on an open flame or other ignition source
 P251 Pressurized container - Do not pierce or burn, even after use
 P260 Do not breathe dust, mist, vapors or spray
 P264 Wash contacted skin thoroughly after handling
 P271 Use only outdoors or in a well-ventilated area
 P272 Contaminated work clothing should not be allowed out of the workplace
 P280 Wear protective gloves, protective clothing, eye protection, face protection and respiratory protection.
 P321 Specific treatment (see first aid instructions on SDS)
 P362 Take off contaminated clothing and wash before reuse
 P302+P352 IF ON SKIN: Wash with soap and water
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
 P308+P313 IF exposed or concerned: Get medical advice
 P333+P313 If skin irritation or a rash occurs: Get medical advice
 P337+P313 If eye irritation persists: Get medical attention.
 P405 Store locked up
 P403+P233 Store in a well ventilated place. Keep container tightly closed
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 P501 Dispose of contents and container in accordance with local, regional, national and international regulations.

Emergency Overview

Physical Description & Colour: White liquid (when sprayed).

Odour: Organic solvent odour.

Major Health Hazards: Exposure can cause respiratory tract and throat irritation, headaches, shortness of breath and symptoms similar to intoxication. Overexposure can produce severe central nervous system depression, coma and respiratory failure. May cause serious damage to eyes, may cause cancer, may cause heritable genetic damage, may impair fertility, may cause harm to unborn children.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	67-64-1	20-30	1185	2375
Propane/isobutane/n-butane	68476-86-8	20-30	not set	not set
Methyl ethyl ketone	78-93-3	10-20	445	890
Propylene glycol monomethyl ether acetate	108-65-6	5-10	274	548
Talc	14807-96-6	1-5	2.5	not set
Titanium dioxide (dust)	13463-67-7	4.2	not set	not set
Nitrocellulose	9004-70-0	1-5	not set	not set
Methyl isobutyl ketone	108-10-1	1-3	205	307
Toluene	108-88-3	1-5	191	574
Isopropyl alcohol	67-63-0	1-5	983	1230
Maleic modified rosin resin	secret	1-5	not set	not set
Methanol	67-56-1	0.1-1	262	328
Ethyl benzene	100-41-4	0.1-0.5	434	543

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equaled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

SAFETY DATA SHEET

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam or water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses. **Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: -56°C

Upper Flammability Limit: 11.4%

Lower Flammability Limit: 1.0%

Autoignition temperature: 170°C

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include butyl rubber, Teflon, PE/EVAL, Responder and polyvinyl alcohol. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8). Otherwise, not normally necessary. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Take suitable precautions e.g. use of non-sparking equipment to avoid creating sparks or flames which may ignite the spilled material. Leaking gases may form an explosion hazard. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to

persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Acetone	1185	2375
Methyl ethyl ketone	445	890
Propylene glycol monomethyl ether acetate	274	548
Talc	2.5	not set
Methyl isobutyl ketone	205	307
Toluene	191	574
Isopropyl alcohol	983	1230
Methanol	262	328
Ethyl benzene	434	543

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: butyl rubber, Teflon, PE/EVAL, Responder and polyvinyl alcohol.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	White liquid (when sprayed).
Odour:	Organic solvent odour.
Boiling Point:	Solvent boils at 56°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	81.24% w/w
Vapour Pressure:	14.6652 kPa (solvent)
Vapour Density:	2.6
Specific Gravity:	0.823
Water Solubility:	No data.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	170°C

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat, flames and sparks. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed. Protect this product from light.

Incompatibilities: acids, bases, strong oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas in reducing atmospheres. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

Section 11 - Toxicological Information

Toxicity:

May affect liver, kidney and central nervous system with repeated exposure. Prolonged or repeated exposure may cause lung injury. May cause damage to organs through prolonged and repeated exposure. Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. Data available regarding components of this product suggests that it may affect the following organs: eyes, kidneys, liver, lungs, central nervous system, reproductive system, skin, cardiovascular system, gastrointestinal tract and the respiratory system.

Propane/isobutane/n-butane is a SWA Class 2 Mutagen, likely to be mutagenic to humans. Toluene is a SWA Class 3 Reproductive risk.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Acetone	Conc>=20%: Xi; R36
<ul style="list-style-type: none"> Flammable liquid - category 2 Eye irritation - category 2A Specific target organ toxicity (single exposure) - category 3 	
Propane/isobutane/n-butane	Conc>=0.1%: T; R45; R46
<ul style="list-style-type: none"> Gas under pressure Flammable gas - category 1 	
Methyl Ethyl Ketone	No risk phrases at concentrations found in this product
<ul style="list-style-type: none"> Flammable liquid - category 2 Eye irritation - category 2A Specific target organ toxicity (single exposure) - category 3 Specific target organ toxicity (single exposure) - category 3 	
Methyl Isobutyl Ketone	>=1%Conc<20%: Xn; R40
<ul style="list-style-type: none"> Flammable liquid - category 2 Acute toxicity - category 4 Carcinogenicity - category 2 Eye irritation - category 2A Specific target organ toxicity (single exposure) - category 3 	
Toluene	>=0.5%Conc<10%: T; R60; R61
<ul style="list-style-type: none"> Flammable liquid - category 2 Skin irritation - category 2 Specific target organ toxicity (repeated exposure) - category 2 Reproductive toxicity - category 1A 	
Methanol	No risk phrases at concentrations found in this product
<ul style="list-style-type: none"> Flammable liquid - category 2 Acute toxicity - category 3 Acute toxicity - category 3 Acute toxicity - category 3 Specific target organ toxicity (single exposure) - category 1 	

Potential Health Effects

Inhalation:

Short Term Exposure: High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure: Vapours may cause drowsiness and dizziness.

Skin Contact:

Short Term Exposure: Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

Eye Contact:

Short Term Exposure: If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Methyl Isobutyl Ketone is classed 2b IARC - possibly carcinogenic to humans.

Toluene is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 12 - Ecological Information

Insufficient data to be sure of status. This product contains a photochemically active solvent. No testing has been performed regarding the effects of the formulated product on the environment; however, various components are toxic to aquatic organisms such as fish, algae and aquatic invertebrates such as daphnia. Avoid release to waterways.

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service. Not suitable for incineration.

Section 14 - Transport Information

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1950, AEROSOLS

Hazchem Code: 2YE

Special Provisions: 63, 190, 277

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packing Group: Not set

Packing Instruction: P003

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

Section 15 - Regulatory Information

Australia: AIIC (Australian Inventory of Industrial Chemicals)

All the ingredients are listed or exempt.

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AIIC	Australian Inventory of Industrial Chemicals
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)